

PLATE COMPACTORS



- Anti-vibration handle system
- Solid, high-strength steel base plate with curved edges for top performance
- Powered by dependable Honda engine
- Optional impact-resistant water tank for asphalt use
- Gas powered

Model	Plate Size WxL (in.)	Centrif. Force lbs.	Exciter Speed RPM	Max. Fwd Speed ft / min.	Engine Model	HP Rating BHP	Water Tank Cap. qt.	Operating Weight lbs.
MVC64VH	13.8" x 21.3"	2,275	5,600	82	Honda GX-120	4	N/A	151
MVC64VHW	13.8" x 21.3"	2,275	5,600	82	Honda GX-120	4	8.8	157
MVC80VH	17.1" x 22"	3,080	5,600	72	Honda GX-160	5.5	N/A	174
MVC80VHW	17.1" x 22"	3,080	5,600	72	Honda GX-160	5.5	11.5	180

DEMOLITION TOOLS



Model	Net Weight lbs.	L	W	D	Air Hose Size in.	Standard Chuck	Optional Chuck	Bore & Stroke	Blows per Minute
125R Breaker	97	28 <sup>3</sup> / <sub>4</sub> "	16"	6"	<sup>3</sup> / <sub>4</sub> "	1 <sup>1</sup> / <sub>4</sub> " Hex x 6"	1 <sup>1</sup> / <sub>8</sub> " Hex x 6"	2 <sup>5</sup> / <sub>8</sub> " x 5"	1,250
123R Breaker	72 <sup>1</sup> / <sub>2</sub>	26"	16"	6"	<sup>3</sup> / <sub>4</sub> "	1 <sup>1</sup> / <sub>8</sub> " Hex x 6"	1 <sup>1</sup> / <sub>4</sub> " Hex x 6"	2 <sup>1</sup> / <sub>4</sub> " x 5"	1,400
6R Tamper	40	49 <sup>3</sup> / <sub>8</sub> "	3" Body	5 <sup>3</sup> / <sub>4</sub> " Butt	<sup>3</sup> / <sub>4</sub> "	N/A	N/A	1 <sup>1</sup> / <sub>2</sub> " x 5 <sup>1</sup> / <sub>2</sub> "	800
KCB2 Chipper	18	14 <sup>3</sup> / <sub>4</sub> "	8 <sup>1</sup> / <sub>8</sub> "	3 <sup>1</sup> / <sub>8</sub> "	<sup>1</sup> / <sub>4</sub> "	.680 Rd. or .580 Hex	Ball-Type Retainer	1 <sup>1</sup> / <sub>8</sub> " x 2"	2,300



Michael Todd & COMPANY, INC.