

TRAFFIC CONES

see
cone signs
on page 38



Part No.	Height	Weight	Pkg. Qty.
GLO 12	12"	1¼ lbs.	30
GLO 18	18"	3 lbs.	20
GLO 28	28"	7 lbs.	10
GLO 28H	28"	10 lbs.	10
GLO 36	36"	9½ lbs.	10

REFLECTIVE CONE BAR
Adjusts from 48" – 81" and fits all standard 18", 28" and 36" traffic cones; Use to delineate pedestrian areas, define areas of danger or caution in construction areas, or to cordon off confined space work areas. Black & yellow
No. RCB

OPTIONS



No. SL4 4" upper reflective collar
No. SL6 6" upper reflective collar
No. SL4L 4" lower reflective collar
Ask about Custom Stenciling

LOOPER CONES



- Looped handle allows for easy movement and handling of several loopers at one time
- Made of durable bright orange low density polyethylene
- Reinforced handle design prevents cones from sticking when stacked
- Available with 16 and 30 lbs. molded recycled rubber bases
- Available in several reflective sheeting configurations (high performance and diamond grade)
- Recessed areas protect sheeting from being scratched
- Handle has a built in attachment to accept a standard barricade light

Part No.	Description*	Ship. Wt.
46266-CRU-16HP	Looper cone with 16 lbs. base	19 lbs.
46266-CRU-30HP	Looper cone with 30 lbs. base	33 lbs.

*shown with (4) 6" high performance collars

CHANNELIZERS



Channelizer drums are available in rugged, durable high density or impact resistant, reshapeable low density orange polyethylene with UV inhibitors to minimize fading. Drum tested and certified to meet NCHRP-350 crashworthy requirements and meets or exceeds MUTCD specifications.

"D"-shaped drum design minimizes rolling after impact and separation from base. Tapered design allows stacking with or without barricade lights for easy handling and storage. Drum minimum width is 18" throughout its 42" height.

Two mounting holes for optional barricade lights and built-in carrying and dragging handle add to its ease of use.

Available Sheeting Options:
4" or 6" white or orange
Engineer Grade sheeting

4" or 6" white or orange High Intensity sheeting.
4" or 6" white or orange Diamond Grade sheeting.
Please check sheeting specifications in your area.