

ELECTRIC SUBMERSIBLE CENTRIFUGAL PUMPS



- Strain relief cord protection
- Carrying handle
- Thermal overload protection
- Cast iron pump casing for demanding environments
- Oil-filled seal provides positive lubrication when running dry
- Easy cleanout
- Cast iron impeller
- Side discharge

Model	Impeller	Disc. Size in.	Total Head ft.	Cap. GPM	HP	Volt. Phase	Start Amp	Run Amp	Dia. in.	Ht. in.	Wt. lbs.
ST2047	Neoprene Rubber over Cast Iron	2	47	87	1	120V 1Ø	49	9.8	7.4	15.4	33
ST2047B	Neoprene Rubber over Cast Iron	2	47	87	1	230V 1Ø	24.5	4.9	7.4	15.4	33

CENTRIFUGAL PUMPS



- Designed to handle all types of clear water applications
- Discharge port easily rotated 180° by removing (4) bolts
- Cast aluminum body with cast iron nipples for durability
- Plastic fill and drain plugs
- Recoil starter
- Tubular steel frame protects pump and engine
- Oil alert with automatic shut down if oil level is insufficient
- Stainless steel hardware
- Shock mounts isolate vibration
- Optional wheel kit

Model	Suction x Discharge in.	Max. Capacity GPM	Max. Pres. psi	Max. Solids in.	Engine	HP	RPM	Fuel Capacity qt.	Dry Weight lbs.	Dimensions L" x W" x H"
QP204H	2" x 2"	142	46.8	0.5	Honda GX-120	4	3,600	2.6	57	19" x 14" x 16"
QP303H	3" x 3"	245	42.4	0.75	Honda GX-160	5.5	3,600	3.8	77	21.3" x 14.3" x 18"

DIAPHRAGM PUMPS



- Positive displacement design for quick, easy priming
- Oil bath transmission includes built-in 6:1 gear reduction
- Dependable easy starting Honda overhead valve engines
- Wheel kits standard
- Recoil starter

Model	Suction x Discharge in.	Max Capacity GPM	Max. Solids in	Engine	HP	RPM	Fuel Capacity qt.	Dry Weight lbs.	Dimensions L" x W" x H"
MQD2H	2" x 2"	50	1	Honda GX-120	4	3,600	2.6	138	41.5" x 30" x 22"
MQD3H	3" x 3"	90	1.5	Honda GX-120	4	3,600	2.6	139	41.5" x 30" x 22"