

MOTOR GRADER BLADES

Michael Todd & Co., Inc. offers a full line of cutting edges for motor graders.



STANDARD STOCK:

- Curved Double Bevel / Standard Highway Punch (CDB / SHP).
- ForgeTemp® high carbon steel (241–320 BNH) for long wear life.
- Countersunk holes for 5/8" plow bolts.

Special order options include: Max Temp® heat treated (390–475 BNH); Serrated (toothed) grader blades; Curved Single Bevel (CSB); Special hole spacing; Center punching.

Part No.	Size	Hole Spacing	Bolts Required
58X6X5	5/8" x 6" x 5ft	12"	7
58X6X6	5/8" x 6" x 6ft	12"	8
58X6X7	5/8" x 6" x 7ft	12"	9
58X6X8	5/8" x 6" x 8ft	12"	10
58X8X5	5/8" x 8" x 5ft	12"	7
58X8X6	5/8" x 8" x 6ft	12"	8
58X8X7	5/8" x 8" x 7ft	12"	9
58X8X8	5/8" x 8" x 8ft	12"	10
34X6X5	3/4" x 6" x 5ft	6"	11
34X6X6	3/4" x 6" x 6ft	6"	13
34X8X5	3/4" x 8" x 5ft	6"	11
34X8X6	3/4" x 8" x 6ft	6"	13
34X8X7	3/4" x 8" x 7ft	6"	15
34X8X8	3/4" x 8" x 8ft	6"	17

SNOW PLOW BLADES

We offer snow plow edges for most models of snow plows and wings. Edges are precision punched for quick and easy mounting and are produced from the highest quality steels.

Part No.	Size	Spacing	Bolts Required	Bolt Type
12X6X10	1/2" x 6" x 10ft	12"	12	5/8" carriage
12X6X11	1/2" x 6" x 11ft	12"	13	5/8" carriage
58X6X9	5/8" x 6" x 9ft	12"	11	5/8" carriage
58X6X10	5/8" x 6" x 10ft	12"	12	5/8" carriage
58X6X11	5/8" x 6" x 11ft	12"	13	5/8" carriage
58X8X6FSE	5/8" x 8" x 6ft	12"	8	5/8" carriage
58X8X7FSE	5/8" x 8" x 7ft	12"	9	5/8" carriage
58X8X8FSE	5/8" x 8" x 8ft	12"	10	5/8" carriage
58X8X9	5/8" x 8" x 9ft	12"	11	5/8" carriage
58X8X10	5/8" x 8" x 10ft	12"	12	5/8" carriage
58X8X11	5/8" x 8" x 11ft	12"	13	5/8" carriage
58X8X12	5/8" x 8" x 12ft	12"	14	5/8" carriage
34X8X10	3/4" x 8" x 10ft	12"	12	5/8" plow
34X8X11	3/4" x 8" x 11ft	12"	13	5/8" plow
34X8X12	3/4" x 8" x 12ft	12"	14	5/8" plow
1X8X11	1" x 8" x 11ft	12"	13	5/8" plow

BNH = Brinnell Hardness



STANDARD STOCK:

- Flat Square Edge / Standard Highway Punch (FSE / SHP).
- ForgeTemp® high carbon steel (241–320 BNH) for long wear life.
- Holes are square on 1/2" and 5/8" thickness; countersunk holes on 3/4" and 1" thickness.

Special order options include: Surface hardening (589–744 BNH); Mitered ends; Special hole spacing; Countersunk holes

SMALL TRUCK SNOW PLOW BLADES

We stock straight and V-plow blades for:

Blizzard Boss Hiniker Meyer
Northman Polar Western