

LED LIGHTS

WARNING LIGHTS - NORTH AMERICAN



- No. LED625F**
- High impact LED strobe light
 - 360° display
 - (4) User selected flash patterns
 - Flange Base
 - Permanent or magnetic mount



- No. MMBLEDLP**
- Low profile LED mini bar
 - Clear outer lens / 24 high output amber LEDs
 - 5 user selectable patterns
 - Optional 24V or magnetic mount versions available



- No. LED5000**
- Compact surface-mount package with mounting gasket
 - Fully encapsulated circuitry, weatherproof
 - Two heads can be converted for alternating flash patterns
 - Optional "L" mounting bracket available



- No. TA9L-A**
- Deck light
 - (2) Rapid fire LED lamps
 - Flashes back and forth for an attention getting flash pattern
 - Designed for indoor / outdoor use
 - Includes "L" mounting bracket



- No. TA36L-A**
- Direct traffic around slow moving or stopped vehicles
 - (8) LED lamp assembly
 - (3) Modes / (2) Speeds
 - Complete with 25' cable
 - Touch pad controller



- No. 4WABLED**
- (10) 4" round LED lamps
 - (4) Active modes (left, right, center 4 lamps or "all on")
 - Includes 25' cable and 3 rocker switch control
 - Aluminum housing with flange on back for easy flat surface mounting



- No. WBE10** Rectangular for oval heads
No. WBE20 Rectangular for (2) oval heads
No. WBE1R Square for 4" round heads
- Steel weld box precision cut, formed and welded to exacting standards
 - Powder coated black



- No. LEDQO**-* oval
No. LEDQR-* round
- (21) High impact LEDs
 - (3) Steady burn LEDs in center
 - Includes rubber grommet and 3 wire pigtail
 - Flush mount



- No. CLK2H45** 45 watt / (2) head / (2) 25' cables
No. CLK4H45 45 watt / (4) head / (2) 15' (2) 25' cables
No. CLK4H70 70 watt / (4) head / (2) 15' (2) 25' cables
- Strobe light bulbs install in existing corner light housings

Model No.	Description	FPM	Height - Diameter	Weight	Voltage	Amp @ 12V	Warranty
LED625F	LED strobe	User select	4½" x 5½"	1.5 lbs.	12/24V	1.60	5 year
MMBLEDLP	Lo-Profile LED mini bar	User select	2¾" x 8½" x 17¼"	10 lbs.	12-24	6.00	5 year
LED5000-*	LED surface mount	User select	4½" x 2¼" x 2"	2 lbs.	12/24V	1.75	5 year
TA9L-A	LED deck	160	2¼" x 8"	3 lbs.	12/24V	0.25	5 year
TA36L-A	LED bar	Sequencing	2¼" x 3" x 34½"	12 lbs.	12/24V	2.20	5 year
4WABLED	LED directional arrow	60 single	13" x 53"	10 lbs.	12/24V	2.25	5 year
LEDQO-A	LED flush mount	70 Quad	6¼" x 2¼"	1 lb.	12/24V	0.33	5 year
LEDQR-A	LED Flush mount	70 Quad	4" Round	1 lb.	12/24V	0.33	5 year

* Available in amber, clear, red and blue