

TWIST LINK CROSS CHAIN – CONTINUOUS - HARDENED



Part No.	Material Diameter		Wt. per 100 Ft. (Lbs.)	Pitch Length	Cartons	Drums
	Inches	Decimal			Ft./Pkg.	Ft./Pkg.
CROSS 3/0	1 ³ / ₆₄	0.207	35	0.920	100	–
CROSS 5/0	1 ⁵ / ₆₄	0.234	47	1.000	100	–
CROSS 6/0	9 ³ / ₃₂	0.281	65	1.250	100	800
CROSS 7 NEW	5 ¹ / ₁₆	0.312	77	1.390	100	700
CROSS 7/0	5 ¹ / ₁₆	0.312	88	1.090	100	700
CROSS 9/0	3 ³ / ₈	0.375	124	1.265	100	500
CROSS 9T	3 ³ / ₈	0.375	115	1.650	100	500
CROSS SQ11	3 ³ / ₈	0.375	156	–	–	300
CROSS 11/0	7 ¹ / ₁₆	0.437	166	1.563	50	300
CROSS 14/0	1 ⁷ / ₃₂	0.531	254	1.734	50	200

SQUARE STRAIGHT LINK ALLOY CROSS CHAIN – CONTINUOUS - HARDENED



Part No.	Material Diameter	Wt. per 100 Ft. (Lbs.)	Pitch Length	Cartons	Drums
				Ft./Pkg.	Ft./Pkg.
CROSS SL7MM	7 mm	90	0.955	100	100
CROSS SL8MM	8 mm	112	1.15	100	100
CROSS SL10MM	10 mm	160	1.49	100	300

STRAIGHT LINK SIDE CHAIN – CONTINUOUS - UNHARDENED



Part No.	Material Diameter		Wt. per 100 Ft. (Lbs.)	Pitch Length	Cartons	Drums
	Inches	Decimal			Ft./Pkg.	Ft./Pkg.
SIDE 2/0*	3 ¹ / ₁₆	0.192	27	1.296	100	–
SIDE 4/0	7 ¹ / ₃₂	0.218	34	1.390	100	–
SIDE 6/0	9 ³ / ₃₂	0.281	60	1.810	100	1000
SIDE 7/0	5 ¹ / ₁₆	0.312	68	1.920	100	800
SIDE TRAC7	5 ¹ / ₁₆	0.312	66	2.127	100	800
SIDE 9/0	3 ³ / ₈	0.375	104	2.170	100	500
SIDE 11/0	7 ¹ / ₁₆	0.437	140	2.330	100	350

*Standard finish is zinc plated.

CHAIN REPAIR PARTS

WIRE DIAMETER CROSS REFERENCE CHART				
Trade Size	Decimal Diameter	Fractional	Metric	Actual Min./Max.
#1	.162	–	4.11mm	.160/.163
1/0	.177	1 ¹ / ₆₄	4.50mm	.174/.177
2/0	.192	3 ¹ / ₁₆	4.88mm	.189/.193
3/0	.207	1 ³ / ₆₄	5.26mm	.205/.208
4/0	.218	7 ¹ / ₃₂	5.54mm	.210/.213
.234	.234	1 ⁵ / ₆₄	5.94mm	.234/.238
6/0	.281	9 ³ / ₃₂	7.14mm	.275/.279
7/0	.312	5 ¹ / ₁₆	7.92mm	.298/.303
9/0	.375	3 ³ / ₈	9.53mm	.364/.369
11/0	.437	7 ¹ / ₁₆	11.10mm	.425/.430
14/0	.531	1 ⁷ / ₃₂	13.49mm	.520/.525