# TRUCK SAFETY

# TRUCK SAFETY BACK-UP ALARMS



### No. LDA50

The best-selling alarm in the industry.

- · Single sound level
- 97 decibels
- 12 volt system
- · SAE J994 Types C
- Shipping weight: 12 oz.
- Dimensions: 41/2"L x 1"D x 41/2"H



# No. 240

- Single sound level
- 97 decibels
- 12-24 volt systems
- SAE J994 Types C
- Shipping weight: 10 oz.
- Dimensions: 41/2"L x 1"D x 41/2"H



# No. 45AA

Housed in rugged, die-cast aluminum.

- Manually adjustable sound
- 87 and 107 decibels
- 12-24 volt systems
- SAE J994 Types B & D
- Vertical or horizontal mounting
- Shipping weight: 3 lbs.
- Dimensions: 51/2"L x 33/4"D x 43/4"H

# **SAFETY TRIANGLE KIT**



### No. 0100031

- Three (3) Triangles packed in a plastic case with handle
- Shipping weight: 14.5 lbs.

# **RUBBER WHEEL CHOCKS**



### No. 2048WC

- Maximum durability and skid protection especially under adverse weather conditions.
- Zinc-plated eyebolt.
- · Weight: 9 lbs.

# **RATCHET STRAP ASSEMBLIES**

2" ratchet strap assemblies with long, wide handle

| Part No. | End Fitting | Width | Length | MBS*        | WLL^       |
|----------|-------------|-------|--------|-------------|------------|
| 10R27FHY | Flat Hook   | 2"    | 27 ft  | 10,000 lbs. | 3,335 lbs. |
| 10R27JHY | J-Hook      | 2″    | 27 ft  | 10,000 lbs. | 3,335 lbs. |



^ WLL = working load limit

# **TOW ROPES**

3-strand lightweight nylon tow ropes for heavy duty use. Available with hooks or loops

| Part No. | Size       | Hooks /<br>Loops | Application                | Wt. / ea |
|----------|------------|------------------|----------------------------|----------|
| TH2078   | 7⁄8″ x 20′ | 2 hooks          | Large cars, small pick ups | 8 lbs.   |
| TH2010   | 1" x 20'   | 2 hooks          | Up to 100 HP               | 10 lbs.  |
| NH20125  | 1¼" x 20'  | 2 loops          | Up to 150 HP               | 8 lbs.   |
| NH2515   | 1½" x 25'  | 2 loops          | 75 to 150 HP               | 15 lbs.  |
| NH2520   | 2" x 25'   | 2 loops          | 150 to 300 HP              | 25 lbs.  |
| NH25225  | 2¼" x 25'  | 2 loops          | 275 to 400 HP              | 36 lbs.  |



<sup>\*</sup> MBS = minimum break strength