


REVOLVING LIGHTS

		
<p>No. TR4</p> <ul style="list-style-type: none"> • Light duty - low cost • 12V magnetic mount • 90 lb. magnet pull • Coiled cord & plug-in • 55W Halogen bulb with reflector 	<p>No. 250</p> <ul style="list-style-type: none"> • Heavy duty • 12V or 24V (specify) • Heavy duty motor and gear shaft with enclosed power feed attached directly to sealed beam head • Stainless steel base 	<p>No. MBTR Revolving</p> <ul style="list-style-type: none"> • Features two 55W halogen revolving bulbs providing up to 2000 hours use • Center diamond mirror • Polycarbonate outer dome • Permanent or magnetic mount

STROBE LIGHTS

		
<p>No. Q350</p> <ul style="list-style-type: none"> • Quad flash strobe • Micro-Burst™ super sonic welded strobes • Multivoltage 12/48V • 3 year warranty • Permanent or magnetic mount 	<p>No. Q625</p> <ul style="list-style-type: none"> • Quad flash strobe • Low profile housing • Black polycarbonate lens • Bright, powerful and economical • Dual voltage 12/24V • Permanent or magnetic mount 	<p>No. Q1250</p> <ul style="list-style-type: none"> • Quad flash strobe • Heavy duty deluxe light for heavy equipment • Stainless steel base and band • Two dome (inner and outer) system • Large 9" diameter light • Dual Voltage 12V/24V
		
<p>No. MB625 Strobe</p> <ul style="list-style-type: none"> • Alternating quad flash display • Various outer/inner dome colors available • Center diamond mirror • Polycarbonate outer lens • Permanent or magnetic mount 	<p>LEVELING BRACKETS</p> <ul style="list-style-type: none"> • LB1 and LB2 include mounting plate • LB1 Leveling bracket, up to 6" diameter • LB2 Leveling bracket, up to 9" diameter • LB5 Leveling bracket, up to 23" width including MB series mini-bars 	<p>ACTION BARS</p> <ul style="list-style-type: none"> • Anodized aluminum crossbars • 1.5" x 1.5" standard cross bar • Specify 54", 60" or 66" size • Specify for vehicles with or without rain gutters

Model	Type	FPM	Voltage	Weight	Height - Diameter	Amp @ 12V	Dome No.	Bulb No.	Candellas / Joules
TR4	Revolving	135	12V	2.75 lbs.	5¼" x 5½"	4.5	BBL-33*	HA-77	65000
250	Revolving	90	12V or 24V	8 lbs.	9" x 9"	4.5	250-33*	250-77	105000
MBTR	Rev'g Bar	135	12V	10 lbs.	5¼" x 8" x 23"	10	MB-33*	HA-77	110000
Q350	Strobe	65 Quad	12/24V	2 lbs.	4" x 4.6"	0.8	N/A	N/A	5.25
Q625	Strobe	75 Quad	12/24V	2 lbs.	4½" x 5½"	3.0	500-33*	L3-77	10
Q1250	Strobe	80 Quad	12/24V	7 lbs.	9" x 9"	3.5	250-33* (out) 500-33* (in)	ST-77	25
MB625	Strobe Bar	150 Quad	12/24V	10 lbs.	5¼" x 8" x 23"	3.0	MB-33*	I3-77	10.75

* Add letter to indicate dome color: (A) amber, (B) blue; (C) clear; (R) red

WARNING LIGHTS - NORTH AMERICAN

LED LIGHTS

WARNING LIGHTS - NORTH AMERICAN



- No. LED625F**
- High impact LED strobe light
 - 360° display
 - (4) User selected flash patterns
 - Flange Base
 - Permanent or magnetic mount



- No. MMBLEDLP**
- Low profile LED mini bar
 - Clear outer lens / 24 high output amber LEDs
 - 5 user selectable patterns
 - Optional 24V or magnetic mount versions available



- No. LED5000**
- Compact surface-mount package with mounting gasket
 - Fully encapsulated circuitry, weatherproof
 - Two heads can be converted for alternating flash patterns
 - Optional "L" mounting bracket available



- No. TA9L-A**
- Deck light
 - (2) Rapid fire LED lamps
 - Flashes back and forth for an attention getting flash pattern
 - Designed for indoor / outdoor use
 - Includes "L" mounting bracket



- No. TA36L-A**
- Direct traffic around slow moving or stopped vehicles
 - (8) LED lamp assembly
 - (3) Modes / (2) Speeds
 - Complete with 25' cable
 - Touch pad controller



- No. 4WABLED**
- (10) 4" round LED lamps
 - (4) Active modes (left, right, center 4 lamps or "all on")
 - Includes 25' cable and 3 rocker switch control
 - Aluminum housing with flange on back for easy flat surface mounting



- No. WBE10** Rectangular for oval heads
No. WBE20 Rectangular for (2) oval heads
No. WBE1R Square for 4" round heads
- Steel weld box precision cut, formed and welded to exacting standards
 - Powder coated black



- No. LEDQO**-* oval
No. LEDQR-* round
- (21) High impact LEDs
 - (3) Steady burn LEDs in center
 - Includes rubber grommet and 3 wire pigtail
 - Flush mount



- No. CLK2H45** 45 watt / (2) head / (2) 25' cables
No. CLK4H45 45 watt / (4) head / (2) 15' (2) 25' cables
No. CLK4H70 70 watt / (4) head / (2) 15' (2) 25' cables
- Strobe light bulbs install in existing corner light housings

Model No.	Description	FPM	Height - Diameter	Weight	Voltage	Amp @ 12V	Warranty
LED625F	LED strobe	User select	4 1/2" x 5 1/2"	1.5 lbs.	12/24V	1.60	5 year
MMBLEDLP	Lo-Profile LED mini bar	User select	2 3/4" x 8 1/2" x 17 1/4"	10 lbs.	12-24	6.00	5 year
LED5000-*	LED surface mount	User select	4 1/2" x 2 1/4" x 2"	2 lbs.	12/24V	1.75	5 year
TA9L-A	LED deck	160	2 1/4" x 8"	3 lbs.	12/24V	0.25	5 year
TA36L-A	LED bar	Sequencing	2 1/4" x 3" x 34 1/2"	12 lbs.	12/24V	2.20	5 year
4WABLED	LED directional arrow	60 single	13" x 53"	10 lbs.	12/24V	2.25	5 year
LEDQO-A	LED flush mount	70 Quad	6 1/4" x 2 1/4"	1 lb.	12/24V	0.33	5 year
LEDQR-A	LED Flush mount	70 Quad	4" Round	1 lb.	12/24V	0.33	5 year

* Available in amber, clear, red and blue



- No. LL1200 Tuf-Flash®**
- Designed for forklift trucks
 - Provides less distraction for operators
 - Polycarbonate lens with metal cap
 - Heavy duty aluminum flanged base for over or under mounting
 - Double flash strobe



- No. LL9200 Fire Flash® II**
- Multi-purpose cost effective light
 - Vibra-Shield™ internal shock absorber
 - Low profile lens
 - Heavy duty aluminum flanged base
 - Double flash strobe
 - Available magnetic mount



- No. LL400I Star Flash IV**
- High powered quad flash strobe light
 - Industrial/Construction applications
 - Low profile lens
 - Patented universal mounting permanent or 1" pipe mount
 - Available magnetic mount



- No. LL800I Astro Flash® II**
- Field proven, strobe light
 - Ideal for construction equipment
 - Anodized aluminum case
 - Patented universal permanent mount or 1" pipe mount
 - Heavy duty Xenon flash tube
 - Meets SAE requirements
 - Available magnetic mount



- No. LL200I Nova Flash® IV**
- Extremely powerful quad flash
 - Hi/Low feature for optimal light output
 - Anodized aluminum case
 - Patented universal permanent mount or 1" pipe mount
 - Heavy duty Xenon flash tube
 - Available magnetic mount



- No. Q3000 Quantum Flash™ LED**
- Utilizes 6 of the brightest LEDs available
 - Multiple flash pattern
 - Maintenance free
 - Holds up under extreme vibration
 - Rated 100,000 hour life / 5 year warranty



- No. 4HCLH Hide-Away™ Strobe**
- (4) clear Xenon strobe heads
 - 4-head high intensity power supply
 - User selectable Hi/Lo intensity
 - Double and quad flash patterns
 - (4) 15' shielded cables
 - Mount directly into head and tail-light housings
 - Shipping weight: 5 lbs.



- No. 6105HS**
- Polycarbonate base and lens.
 - 5"H x 16"L x 10½"W
 - 2 rotators, 1 flat mirror
 - 400 flashes / minute / 12V DC
 - Also available in magnetic mount
 - Shipping weight: 5 lbs.









- No. AS847H ArrowStik®**
- Directional Arrow
 - Extruded aluminum frame
 - Polycarbonate lens
 - 12V DC. 9 amp draw
 - 2¾"H x 47"L x 4¾"W
 - (8) 28W incandescent (1156) bulbs
 - Shipping weight: 16 lbs.



Model No.	Description	FPM	Height - Diameter	Weight	Voltage	Amp @ 12V	Amber Dome No.	Bulb No.	Joules
LL1200	Strobe	72DF	4½" x 7¾"	5 lbs.	12-48	2.0	T13009	T13074	5
LL9200	Strobe	72DF	4⅞" x 6"	2 lbs.	12/24V	1.8	T13063	T15597	9
LL400I	Strobe	72QF	6⅝" x 6¼"	3.7 lbs.	12/24V	2.5	T02244	T05606	14
LL800I	Strobe	72DF	6⅝" x 6¼"	3.8 lbs.	12/24V	2.5	T02244	T05606	16
LL2000	Strobe	72QF	6⅝" x 6¼"	3.8 lbs.	12/24V	2.5	T02244	T05606	20
Q3000	LED	Variable	6¾" x 5"	1.75 lbs.	12/24V	0.5	T08094	N/A	N/A

BARRICADE LIGHTS

BARRICADE LIGHTS & BATTERIES

		
<p>TYPE A</p> <ul style="list-style-type: none"> • Meets MUTCD requirements & ITE specs in 12V configuration • 7" polycarbonate lens with advanced optics • Dependable circuitry coated for protection against weather • Yellow high-density polyethylene case, UV stabilized • Anti-theft bolt protector available • Holds (2) 6V spring top batteries (not included) • 10 lights / carton • Shipping weight: 21 lbs. <p>PART No. DESCRIPTION</p> <p>FLASHER 2 6V flasher with solar switch</p> <p>FLASHER 5 12V flasher with solar switch</p>	<p>Y2K LED</p> <ul style="list-style-type: none"> • LED (Light Emitting Diode) / D-Cell technology • Corrosion resistant stainless steel battery contacts • 3-way switch standard (off, flashing, steady burn) • Holds (4) D-cell batteries (not included) • 10 lights / carton • Shipping weight: 20 lbs. <p>No. Y2K</p>	<p>SOLAR POWERED</p> <ul style="list-style-type: none"> • High intensity LED • 65 FPM (flashes / minute) • 3-way switch (flashing, steady, off) • Rechargeable lead acid battery • Single charge provides 5 nights of operation • Fully compliant with MUTCD specification 6E-5 • Fully compliant with ITE specifications for flashing / steady burn warning lights • Operation life up to 5 years • Tamper proof hardware • 10 lights / carton <p>No. Maverick</p>
		
<p>212 LED TYPE "B" LIGHT</p> <ul style="list-style-type: none"> • Meets I.T.E. and MUTCD Standards • Polycarbonate lenses and high impact polypropylene housing • Available for 6V batteries (shown) and D-cell batteries • Polycarbonate hood • Also available with detachable head • Shipping weight 3 lbs. <p>No. 212</p>	<p>FLARE-LITE EMERGENCY LIGHT</p> <ul style="list-style-type: none"> • Portable LED light with stand • High intensity output from 12 LED's • Energy efficient 1000 hours operation on (2) 6V batteries (not included) • Folding legs and carrying handle for easy transport and storage • Police / Emergency - White stand / light is white case w/red lens • School - Yellow stand / light is yellow case w/ amber lens • Shipping weight 5 lbs. <p>No. Flare</p>	<p>PERSONAL SAFETY LIGHT™</p> <ul style="list-style-type: none"> • 360° LED beacon • Features 24 ultra bright LEDs • 60 triple flashes / minute • Compact design 4½" D x 4¾" H • 300-400 hours on 2 "D" batteries • Magnet mount base included <p>No. PSLM2-A Amber</p> <p>No. PLLM2-R Red</p> <p>No. PS-HDL Optional 4" H x 1¾" D handle can be attached to PSLM2 light to make a great traffic cone light!</p>

BATTERIES

	
<p>No. 6V-HD</p> <ul style="list-style-type: none"> • 6V spring terminal battery • Heavy duty industrial grade • 12 batteries / case • Shipping weight: 17 lbs. 	<p>No. AL-D</p> <ul style="list-style-type: none"> • Alkaline D-cell batteries • For high drain frequent use devices • 6 batteries / package • Sold in package quantities only • Shipping weight: 2 lbs.



ARROW BOARDS

No. WTSP55-LSAC Solar Traffic Directors™

- Powder coated paint
- Control box with slam latch lid and rear cable protection cover
- Steel battery box
- Reduced power consumption
- Optional auto lock stabilizer pins

TRAILER SPECIFICATIONS

- Axle assembly with leaf springs: 2000 lbs. capacity
- 15" automotive tires
- Heavy duty winch with safety brake allows one person to raise arrow board
- Single locking device to hold arrow board in place while in operation or travel modes
- Optional ring or combo ball/pintle hitches available
- Optional auto locking pins for stabilizer legs
- Solar panel(s) wattage: 50/55 (other panels/wattages available)
- Battery bank capacity: 450 AMP-HR
- 25 Lamps
- 12 Arrow modes

CONTROLLER SPECIAL FEATURES

- Positive drive voltage system (voltage to lamps only when they flash)
- 25 light models have 12 arrow functions (see below)
- Lockable weather resistant aluminum box
- Resettable dual circuit breakers
- Low voltage disconnect with indicator
- Solar panel voltage regulator with indicator
- Automatic and manual dimming functions
- Reverse polarity protection



FLASHING MODEL MODES	SEQUENTIAL MODEL MODES		
	FIRST PULSE	SECOND PULSE	THIRD PULSE
CORNER CAUTION	SEQUENTIAL STEM ARROW LEFT & RIGHT		
CAUTION BAR	SEQUENTIAL ARROW LEFT & RIGHT *		
LEFT & RIGHT	SEQUENTIAL CHEVRON ARROW LEFT & RIGHT *		
DOUBLE ARROW	ALTERNATING	DIAMONDS *	

* = REQUIRES 25 LIGHT ARROW BOARD
 • ALL MODES HAVE FLASHING RATE OF 30-40 PER MINUTE
 • CONSULT FACTORY FOR OPTIONAL ARROW MODES NOT SHOWN

Arrow Modes



Battery Box



Controller



CAUTION BEACONS

No. WCBSZ-55-3L

- Great for school zones
- Input voltage: 11.5 VDC to 25 VDC
- Dual alternating lamp flasher 50/60 flashes per minute with LED indicators
- Solar panel regulator rated 25A at 12 VDC, temperature compensation

SCHOOL ZONE BEACON SET

- (2) 12" LED heads and (1) 8" LED rear head
- Aluminum enclosure
- Police lock
- Gel cell battery
- 40 / 55 watt tilted solar panel
- 365 day timer
- Alternating flasher with solar regulation and low voltage disconnect built in
- Sign not included

ARROW BOARDS