

WIDE BASE TRUCK CABLE CHAINS

Tire Sizes				Part No.	Wt./Pr. Lbs.	Replacement Cross Chain	Cross Chain per 1/2 Pair
8.25-15LT	P265/75R16	235/80R17LT	275/65R17	3010*	14	8825	13
10-15LT	245/85R16LT	245/75R17LT	235/75R17.5				
265/70R15LT	265/70R16LT	255/60R17	275/55R18				
265/75R15LT	265/75R16LT	P255/70R17	275/45R19				
305/50R15	265/80R16LT	P265/65R17	255/50R20				
31X10.50-15LT	275/70R16LT	P265/70R17	265/50R20				
33X10.50-15	295/50R16LT	265/70R17LT	275/40R20				
P265/70R16	P235/70R17	275/60R17	275/45R20				
PR78-15	PR78-16	33X13.50-16	285/60R18	3027*	12	8853	11
11-15LT	12-16.5LT	34X9-16	285/45R19				
31X11.50-15LT	P285/60R16	31X10.50-16.5LT	275/55R20				
32X11.50-15LT	275/65R16LT	285/60R17	275/60R20				
33X9.50-15LT	285/60R16LT	285/70R17	P285/50R20				
33X13.50-15	32X11.50-16LT	305/45R17					
34X9.50-15LT		P265/60R18					
12-15LT	35X13.5-15	35X13.5-16	10.50/80R18	3029*	14	8859	11
P315/70R15	35X14.5-15	36X13-16	275/70R18LT				
325/60R15	11L16	32X12.50-16.5LT	285/65R18LT				
31X13.5-15	285/70R16LT	33X12.5-16.5	325/60R18				
32X12.50-15	285/75R16LT	33X15.5-16.5	275/65R20LT				
33X12.50R15	295/75R16LT	275/70R17	305/50R20				
33X14-15	305/70R16LT	285/75R17LT	305/55R20				
33X14.50-15	305/85R16LT	295/70R17LT	305/40R22				
		33X12.50-17	305/45R22				
355/80R20	13-22.5	15-22.5	385/65R22.5	3055	23	8813	16
38.5X16-15	39.5X18-16.5	15-19.5	38X15.50-50	3065	22	8815	13
39.5X18-15	38X15.5-18	40X15.50-22		3069	24		13
425/65R22.5	445/50R22.5	455/55R22.5		3071	26		14
445/65R19.5	16.5-22.5						



* Now meets SAE Class S requirements

WIDE BASE CABLE CHAINS

RULES FOR USING TIRE CHAINS

****IMPORTANT** PRE FIT CHAINS PRIOR TO ACTUAL USE**

For Your Convenience & Safety:

- Consult owner's manual to see if chains can be used on your vehicle.
- Make certain your tire chains are properly sized for your tires. A proper fit is key to performance.
- Follow directions for installing tire chains. Apply as tightly as possible by hand for maximum chain life.
- Be sure to pull off highway to a safe place before installing, servicing or removing tire chains.
- Do not deflate tires to install tire chains.
- Drive approximately ¼ mile. Stop and retighten. Extra links may be cut or preferably retained on the fastener arm. Keep chains tight to snug throughout the operation. Only after retightening may rubber adjusters be applied. **DO NOT USE** adjusters on "all cable type" chains.
- Do not exceed 30 M.P.H. Accelerate and decelerate slowly. Avoid spinning or locking of wheels.
- If a cross chain should fail, stop immediately. Repair or remove. **DO NOT** drive with a broken chain.
- Avoid hitting curbs with tire chains.

NORMAL (Chains installed as tight as possible by hand.)	
	30 MPH – Max. Chain Life
	40 MPH – 57% Chain Life
	50 MPH – 31% Chain Life
LOOSE (Chains loosened by one link each side.)	
	30 MPH – 50% Chain Life
	40 MPH – 16% Chain Life
	50 MPH – 7% Chain Life